

(12) United States Design Patent (10) Patent No.:

O'Loughlin et al.

(45) Date of Patent:

US D564,405 S ** Mar. 18, 2008

(54) FLAGPOLE REFLECTOR

(75) Inventors: Robert F. O'Loughlin, Madison, WI

(US); Michael D. Plitman,

Minneapolis, MN (US); Daniel Steiner,

Waunakee, WI (US); Wayne Timberman, Carmel, IN (US)

Golf Solutions I, L.L.C., Madison, WI (73) Assignee:

(US)

Term: 14 Years

(21) Appl. No.: 29/276,640

Jan. 31, 2007 (22) Filed:

(52) U.S. Cl. D11/181 (58) Field of Classification Search D11/165-167,

D11/180-183; 116/173-175, 202; D10/70; D21/759, 790; 362/190, 296

See application file for complete search history.

(56)References Cited

D242,775 S * 12/1976 Williams, Jr. D10/70

(Continued)

U.S. PATENT DOCUMENTS

OTHER PUBLICATIONS

Internet World Wide Web Page, www.laserlinkgolf.com/ smartyPressRelease.htm, dated Jan. 12, 2005.

Primary Examiner—Ian Simmons Assistant Examiner-Anhdao Doan

(74) Attorney, Agent, or Firm-Foley & Lardner LLP

(57)**CLAIM**

We claim the ornamental design for a flagpole reflector, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of the claimed design;

FIG. 2 is a first side view of the embodiment of FIG. 1;

FIG. 3 is a second side view of the embodiment of FIG. 1, with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 2;

FIG. 4 is a third side view of the embodiment of FIG. 1, with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 3;

FIG. 5 is a fourth side view of the embodiment of FIG. 1, with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 4;

FIG. 6 is a top view of the embodiment of FIG. 1;

FIG. 7 is a bottom view of the embodiment of FIG. 1:

FIG. 8 is a perspective view of a second embodiment of the claimed design;

FIG. 9 is a first side view of the embodiment of FIG. 8;

FIG. 10 is a second side view of the embodiment of FIG. 8, with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 9;

FIG. 11 is a third side view of the embodiment of FIG. 8, with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 10;

FIG. 12 is a fourth side view of the embodiment of FIG. 8. with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 11;

FIG. 13 is a top view of the embodiment of FIG. 8;

FIG. 14 is a bottom view of the embodiment of FIG. 8;

FIG. 15 is a perspective view of a third embodiment of the claimed design;

FIG. 16 is a first side view of the embodiment of FIG. 15;

FIG. 17 is a second side view of the embodiment of FIG. 15, with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 16;

FIG. 18 is a third side view of the embodiment of FIG. 15. with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 17;

FIG. 19 is a fourth side view of the embodiment of FIG. 15. with the flagpole reflector rotated approximately 90 degrees from the view of FIG. 18;

FIG. 20 is a top view of the embodiment of FIG. 15; and,

FIG. 21 is a bottom view of the embodiment of FIG. 15.

The broken lines in FIGS. 1-5, 7-12, 14-19, and 21 are for illustrative purposes only and form no part of the claimed design.

1 Claim, 9 Drawing Sheets

